

## EXTERIOR INSULATION AND FINISH SYSTEM (EIFS) REQUEST

<b>LOCATION (Address):</b>		
Builder Name:	Builder Address:	
<b>SYSTEM DESIGN</b>	New Construction <input type="checkbox"/> Retrofit <input type="checkbox"/>  Manufacturer _____  Manufacturer's system name _____  Does the EIFS system comply with CAN/ULC-S716 1, 2 & 3? Yes <input type="checkbox"/> No <input type="checkbox"/> CCMC Listing or Report # _____	<b>CONSTRUCTION</b>
<b>LOCATION</b>	Walls to have EFIS applied North <input type="checkbox"/> South <input type="checkbox"/> East <input type="checkbox"/> West <input type="checkbox"/>  Other _____  Is the EIFS being used as part of a fire resistance rated wall assembly? ** Yes <input type="checkbox"/> No <input type="checkbox"/> **For walls less than 1.2 m (48 in) from a property line, not adjacent to a street or public thoroughfare, Article 9.10.15.5 of the 2015 NBC requires the exposing building face, measured from the exterior wall face, to have a 45 minute fire resistance rating and the entire wall assembly shall comply with sentence 3.1.5.5.(1)(b) when tested in conformance with CAN/ULC-S134**	<b>SYSTEM COMPONENTS</b>
<b>NOTES</b>	It is the responsibility of the contractor to incorporate all accessories and follow the methods specified by the manufacturer and Subsection 9.27.13 of the 2015 NBC. This includes, but is not limited to: water protection barrier (WPB), clearances from heat emitting devices, and placement of expansion joints, reinforcing mesh, closed cell backer rods, flashings, and wall cavity water drainage.  * EIFS that do not comply to CAN/ULC-S716.1, 2 & 3, do not have a drainage cavity, do not have a substrate of the minimum tested thickness, or are mechanically fastened are required to be designed and sealed by a design professional licenced to consult in Saskatchewan.	
<b>CERTIFICATION</b>	Installing Company: _____ ID #: _____  Signed by (Print): _____ Signature: _____  Phone Number : _____ Email Address: _____	